# STP-666 Spin Tissue Processor (vacuum)



## Features:

- 1. Adopting computer to control whole work process, operate brief work stabilization.
- 2. Having exchange jar and change place control draw perch, operate agility brief.
- 3. If lose electric give an alarm, protecting tissue in liquid, obstache, protect function and so on.
- 4. Adopting agitation dehydrate mode, so tissue and solvent, paraffin meet, thereby well effect.
- 5. Screen showing information is English, easy to use.
- Time design range wide:delay time 59hr59min. Each jar working hours longest 59hr59min,Time design least distance 1 min.
- 7. Wax jar adopt constant temperature control system. Temperature precision high: defend pollution, defend canker.
- 8. Adopting 9 slices 1.2Lmedicine aquarium, at any moment observe tissue change at work.
- 9. According to user's need to tailor standby electrical source, after power cut it can work in great, working hours can reach 4—16hours.

#### Technical Data:

- 10. Steps of processing tissue: 12steps.
- 11. Glass container:Quantity—9capacity-1.2L.
- 12. Wax cup: quantity—3capacity—1L.
- 13. Temperature range— $45 \sim 85 \Box \pm 3 \Box$ .
- 14. Process: Each cup working hours— $0\sim$ 59hr59min.
- 15. Delay process— $0\sim$ 59hr59min.

- 16. Vertically reciprocative motion of tissue basket: 3 times/min
- 17. Tissue basket specification: Barrel tissue basket-- ¢ 95x80mm.
- 18. Layer nacelle--- ¢ 95x80mm Five layers.
- 19. Weight: <60kg.
- 20. External dimension: (diameter)660 x (High)550 x 680(Tiptop)mm.
- 21. Rated voltage: 220v,50Hz.

## Accessories:

Standard Setting List

- 22. Reagent bottle 9 pcs
- 23. Paraffin wax tank 3 pcs
- 24. Paraffin wax tank connection line 3 pcs
- 25. Tissue basket 1 pc
- 26. Tissue cassette 20 pcs
- 27. 6. Hexagonal Wrench 1 pc
- 28. 7. Screwdriver 1 pc
- 29. 8. Fuse (5A) 2 pcs
- 30. 9. Power line 1 line

**Optional Accessories** 

Extra paraffin tank

Extra reagent tank

# Package Info

Each instrument packed Wooden Case

Outer Case Dimensions (for machine): 670\*550\*680 mm, Outer Case Dimensions (for tanks): 510\*510\*510mm, Gross Weight: 110 kg